SD Series Features

- Wrench is adjustable to torque value by rotating grip.
- Simple thumbscrew mechanism locks handle to avoid changing torque value while in use.
- Fast adjustment-takes the fewest rotations of any tool to reach full scale!
- Ball bearing rockover assembly assures smooth aperation, enhances repeatability and increases the cycle life of the wrench.
- When preset torque value is reached a strong audible and tactile impulse is emitted.
- Neoprene rubber grip for cushioning and oil/chemical resistance.
- Includes custom molded plastic case (250 ft. lbs. and below).
- Aluminum increment band is color coded: black for inch lbs.; gold for foot lbs.; blue for Newton metre.
- Accuracy of +/- 4% Indicated Value (from 20% to 100% of capacity) meets or exceeds ASME B107.14M, ISO 6789, and AS 28431.
- Includes FREE ISO/IEC 17025 tabulated certification!

SD Fixed Male Square Drive Head Series - English

Part Number	Torque Model	Steps of Capacity	Graduations	Square Drive	Overall Length
810160	2 SD 50I	10-50 in. lbs	1 in. lb.	¼ in.	9.4
810161	2 SD 150I	30-150 in. lbs	2 in. lb.	¼ in.	9.4
810159	3 SD 200I	40-200 in. lbs	2 in. lb.	% in.	9.4
810163	3 SD 750I	150-750 in. lbs	5 in. lb.	% in.	13.6
810167	4 SD 150	30-150 ft. lbs	1 ft. lb.	½ in.	17.0
810600	6 SD 600*	100-600 ft. lbs	5 ft. lb.	¾ in.	36.4

SD Fixed Male Square Drive Head Series - Newton Metre

Part	Torque	Steps of		Square	Overall
Number	Model	Capacity	Graduations	Drive	Length
810601	6 SD 800 Nm*	160-800 Nm	5 Nm	¾ in.	36.4

^{*} Optional extension tube, Part # 853363, can be ordered. Use of the extension requires recalibration of wrench.

Carry and Storage Cases

Strong, durable cases for carrying and storing your S/R brand micrometer adjustable torque wrenches. Fits SDR, SD, and CCM series tools.

Part Number	Size	Туре	Wrench Range	
820122	Small	Molded Plastic	50I-200I, 6 Nm-20 Nm	
			•	
820123	Medium	Molded Plastic	600I-150 ft. lbs., 50 Nm-200 Nm	
820124	Large	Molded Plastic	250 ft. lbs., 300 Nm	
820127	Extra Large	Metal	600-700 ft. lbs., 800 Nm	



Each wrench includes molded plastic case. (250 ft. lbs./300 Nm and below)



Micrometer Adjustable

Fixed Square Drive SD Series