

## 3/8" Sq. Dr. Extensions

#### 1 1/4" to 18" (32mm to 457mm) Length

Part	Male Square	Type of	Overall	Overall Length		
Number	In.	Lock	In.	mm		
EX-374•	3/8	Pin	1 3/8	34		
EX-374-B•	3/8	Ball	1 3/8	34		
EX-376-2•	3/8	Pin	2	51		
EX-376-B-2•	3/8	Ball	2	51		
EX-376-3•	3/8	Pin	3	76		
EX-376-B-3•	3/8	Ball	3	76		
EX-376-4•	3/8	Pin	4	102		
EX-376-B-4•	3/8	Ball	4	102		
EX-376-5•	3/8	Pin	5	127		
EX-376-B-5•	3/8	Ball	5	127		
EX-376-6•	3/8	Pin	6	152		
EX-376-B-6•	3/8	Ball	6	152		
EX-376-8•	3/8	Pin	8	203		
EX-376-B-8•	3/8	Ball	8	203		
EX-376-9•	3/8	Pin	9	229		
EX-376-B-9•	3/8	Ball	9	229		
EX-376-10•	3/8	Pin	10	254		
EX-376-B-10•	3/8	Ball	10	254		
EX-376-12•	3/8	Pin	12	305		
EX-376-B-12•	3/8	Ball	12	305		
EX-376-15•	3/8	Pin	15	381		
EX-376-B-15	3/8	Ball	15	381		
EX-376-18•	3/8	Pin	18	457		

## 3/8" Sq. Dr. Adapters

#### 1/4" to 3/4" **Male Square**



Part	Male	Female	Type of	Overall Length		
Number	Square In.	Square I	n. Lock	ln.	mm	
EX-254•	1/4	3/8	Pin	1 1/4	32	
EX-254-B•	1/4	3/8	Ball	1 1/4	32	
EX-257-2•	1/4	3/8	Pin	2	51	
EX-257-B-2	1/4	3/8	Ball	2	51	
EX-257-3•	1/4	3/8	Pin	3	76	
EX-257-B-3	1/4	3/8	Ball	3	76	
EX-257-4•	1/4	3/8	Pin	4	102	
EX-257-B-4	1/4	3/8	Ball	4	102	
EX-257-5•	1/4	3/8	Pin	5	127	
EX-257-B-5	1/4	3/8	Ball	5	127	
EX-257-6•	1/4	3/8	Pin	6	152	
EX-257-B-6	1/4	3/8	Ball	6	152	
EX-503•	1/2	3/8	Pin	1 1/2	38	
EX-503-B•	1/2	3/8	Ball	1 1/2	38	
EX-507-2•	1/2	3/8	Pin	2	51	
EX-507-3•	1/2	3/8	Pin	3	76	
EX-507-B-3	1/2	3/8	Ball	3	76	
EX-507-4	1/2	3/8	Pin	4	102	
EX-507-B-4	1/2	3/8	Ball	4	102	
EX-507-6	1/2	3/8	Pin	6	152	
EX-507-B-6	1/2	3/8	Ball	6	152	
EX-622	5/8	3/8	Pin	1 1/2	38	
EX-750	3/4	3/8	7/32 Drill Hole	1 1/2	38	
EX-750-B	3/4	3/8	Ball	1 1/2	38	

# 3/8" Sq. Dr. **Universal Adapters**

#### Male Square to Female Square

i ciriaic oquaic								
Part Number	Male Sq. In.	Female Sq. In.	Type of Lock	Overall In.	Length mm	Largest In.	Diameter mm	
MF-27	1/4	3/8	Pin	1 5/16	49	3/4	19	
MF-27-B•	1/4	3/8	Ball	1 5/16	49	3/4	19	
MF-37•	3/8	3/8	Pin	2 1/8	54	3/4	19	
MF-37-B•	3/8	3/8	Ball	2 1/8	54	3/4	19	
MF-38-B•	3/8	3/8	Ball	2 1/2	64	7/8	22	

Universal wrenches must not be used with impact drivers. Maximum operating angle is 30°.

## 3/8" Sq. Dr. Universal **Adapters - Extension**



### Male Square to Female Square

Part No. Standard	Part No. Tension	Male Square In.	Female Square In.	Type of Lock	Largest In.	Diameter mm
KAM-37-3•	KDM-37-3•	3/8	3/8	Pin	3/4	19
-	KDM-37-6•	3/8	3/8	Pin	3/4	19
-	KDM-37-B-	3 3/8	3/8	Ball	3/4	19
KAM-38-6•	KDM-38-6•	3/8	3/8	Pin	7/8	22

Standard lengths are 3", 6", 9" and 12" (76, 152, 229 and 305mm)