

# 1/2" Sq. Dr. **Adapters**

5/8" to 3/4" Male Square

		-				
Part	Male	Female	Type of	Overall Length		
Number	Square In.	Square In	. Lock	ln.	mm	
EX-623•	5/8	1/2	Pin	1 1/2	38	
EX-623-B	5/8	1/2	Ball	1 1/2	38	
EX-626-3•	5/8	1/2	Pin	3	76	
EX-751•	3/4	1/2	7/32 drill hole	1 13/16	46	
EX-751-B•	3/4	1/2	Ball	1 13/16	46	

# 1/2" Sq. Dr. **Universal Adapters**

### 3/8" to 3/4" **Male Square**



Part	Male	Female	Type of	Overall Le	ength	Largest Di	ameter
Number	Sq. In.	Sq. In.	Lock	In.	mm	in.	mm
MF-39•	3/8	1/2	Pin	2 9/16	65	7/8	22
MF-39B•	3/8	1/2	Ball	2 9/16	65	7/8	22
MF-50•	1/2	1/2	Pin	2 11/16	68	1	25
MF-50B•	1/2	1/2	Ball	2 11/16	68	1	25
MF-55•	1/2	1/2	Pin	3 1/16	78	1 1/4	32
MF-55B	1/2	1/2	Ball	3 1/16	78	1 1/4	32
MF-70	3/4	1/2	7/32 drill ho	le 3 5/8	92	1 1/2	38
MF-70B	3/4	1/2	Ball	3 5/8	92	1 1/2	38

Universal wrenches must not be used with impact drivers. Maximum operating angle is 30°.-

### 1/2" Sq. Dr. Universal **Adapters - Extension**



#### 1/2" Male Square

Part Nu	Male	Female	Type of	Large	st Dia.	
Standard	Tension	Sq. In.	Sq. In.	Lock	In.	mm
KHM-37-6•	KNM-37-6	3/8	1/2	Pin	3/4	19
KHM-38-6	KNM-38-6•	3/8	1/2	Pin	7/8	22
KHM-50-6•	KNM-50-6•	1/2	1/2	Pin	1	25
KHM-50-B-6•	KNM-50-B-6	1/2	1/2	Ball	1	25

Universal wrenches must not be used with impact drivers. Maximum operating angle is 30°.

Standard lengths are 3", 6", 9" and 12" (76, 152, 229 and 305mm)

If the tool you need does not appear in this catalog, give us a call. The odds are, we may have what you need as a noncatalog item. If not, our experienced staff of tooling experts can design and manufacture "specials" to meet the needs of your specific application. Give us a call at 1-800-845-5629 or visit our website www.apex-tools.com.