

## LTC Series Features

- The LTC-Series is superb for use on the assembly line AND in field maintenance kits!
- The +/- 4% Accuracy meets or exceeds ASME B107.14M and ISO 6789, and provides the quality your customers demand!
- The pin lock assures positive head connection, yet permits head changeover in seconds!
- Bi-directional versatility obtained by simply removing head, turning wrench over, and replacing head.
- Extremely versatile system permits use of fewer wrenches by connecting to over 100 standard interchangeable heads, plus extensions, adapters, and your own custom heads!
- Excellent audible and tactile impulse when set torque achieved.
- Unique dovetail design transmits the load at right angle from the wrench to the head; exceptional strength and rigidity of connection.
- Light weight new comfort grip provides superior ergonomics, reducing operator fatigue.
- For handle extension, order Extension Adapter P/N 853538 and custom length extension. Details on website.



## Interchangeable Head Preset LTC Series



Over 100 interchangeable heads to choose from without changing torque values. Simply slide the heads on and "lock on quality".

### LTC Dovetail Head Series

Part Number	Model	Torque Capacity*	Weight (lbs.)	Overall Length (in.)
810100	LTC 50I	50 in. lbs./6 Nm/ 58 kgf•cm	0.5	6.9
810011	LTC 150I	150 in. lbs./17 Nm/ 173 kgf•cm	0.5	6.9
810574	LTC OHT**	300 in. lbs./34 Nm/ 346 kgf•cm	0.5	6.9
810016	LTC 300I	300 in. lbs./34 Nm/ 346 kgf•cm	0.75	8.8
810013	LTC 750I	750 in. lbs./85 Nm/ 864 kgf•cm	1.0	12.6
810014	LTC 1800I	1800 in. lbs./150 ft. lbs./ 204 Nm/21 kgf•m	1.25	15.9
810334	LTC 3600I	3600 in. lbs./300 ft. lbs./ 407 Nm/41 kgf•m	5.5	24.3
810137	LTC 4800I	4800 in. lbs./400 ft. lbs./ 542 Nm/55 kgf•m	8.25	34.3

\* Minimum capacities of preset tools can be calculated at 20% of full capacities.

\*\* For this tool only, minimum capacity is 50% of maximum capacity.

